

# SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-80200S



# ODA

TECHNOLOGIES  
www.odacore.com

Parameter			Specifications	
Output rating(@0℃ ~ 40℃)			0 to 80V / 0 to 200A	
Output WATT			16 KW	
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.2% + 400mV	
	Current		0.2% + 1A	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.2% + 400mV	
	Current		0.2% + 1A	
Ripple and Noise(20Hz to 20MHz)	Voltage		≤ 20mVp-p	
	Current		≤ 10mArms	
Load Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 80mV	
	Current		0.01% + 10mA	
Line Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 80mV	
	Current		0.01% + 10mA	
Resolution	Programming/Readback		≤ 20mV / ≤ 50mA	
	Display Meter		100mV(3-DIGIT) / 1A(3-DIGIT)	
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage		0.02% + 15mV	
	Current		0.05% + 100mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage		0.1% + 10mV	
	Current		0.2% + 10mA	
Transient Response Time			Less than 50μs for output to recover to within 50mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 120ms	
		Falling time	≤3.6s	
	Half load	Rising time	≤ 120ms	
		Falling time	≤ 15ms	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤0V ~ ≥ -0.3V	
	Voltage Output Setting		No overshoot, No undershoot	
Remote Interface			RS232C Standard (RS485 Option)	
Programming Language			SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting	10ms	
		Voltage & Current Query	12ms	
	Measurement	Voltage & Current Query	15ms	
	The Other	Setting & Query	32ms	
State Storage Memory			Five user-configurable(voltage,current)stored states	
Operation Temperature Range			0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling			Isolation AC & DC FAN	
Output Terminal Isolated (maximum, from chassis ground)			±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard		단상 220V ± 10% 50~60Hz	
	Option		3상 380V ± 10% 50~60Hz	
			단상 100V ± 10% 50~60Hz	
			단상 230V ± 10% 50~60Hz	
Calibration Interval	Recommended		1 year	
Dimensions			600mm(W) * 1600mm(H) * 70mm(D)	
Maximum Input Power(full load)			41102.6W	
Weight	Net weight		300kg	
	Gross weight		320kg	

※ 주문자 사양 모델은 spec변경이 이루어질 수 있습니다.