

# SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-50100S



# ODA

TECHNOLOGIES  
www.odacore.com

Parameter			Specifications	
Output rating(@0℃ ~ 40℃)			0 to 50V / 0 to 100A	
Output WATT			5 KW	
Programming Accuracy	Voltage		0.3% + 300mV	
(@25℃ ±5℃)±(%of output + offset)	Current		0.2% + 500mA	
Readback Accuracy	Voltage		0.3% + 300mV	
(@25℃ ±5℃)±(%of output + offset)	Current		0.2% + 500mA	
Ripple and Noise(20Hz to 20MHz)	Voltage		≤ 10mVp-p	
	Current		≤ 10mArms	
Load Regulation	Voltage		0.01% + 30mV	
	Current		0.01% + 10mA	
Line Regulation	Voltage		0.01% + 30mV	
	Current		0.01% + 10mA	
Resolution	Programming/Readback		≤ 15mV / ≤ 25mA	
	Display Meter		100mV(3-DIGIT) / 1A(3-DIGIT)	
Temperature Coefficient ±(%of output + offset)	Voltage		0.02% + 20mV	
After a 30-minute warm-up	Current		0.05% + 100mA	
Stability ±(%of output + offset)	Voltage		0.1% + 20mV	
After a 1 hour warm-up	Current		0.2% + 100mA	
Transient Response Time			Less than 50μs for output to recover to within 50mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 400ms	
		Falling time	≤ 5s	
	Half load	Rising time	≤ 400ms	
		Falling time	≤ 400ms	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤-0.8V	
	Voltage Output Setting		No overshoot, No undershoot	
Remote Interface			RS232C Standard (RS485 Option)	
Programming Language			SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting		10ms
		Voltage & Current Query		12ms
	Measurement	Voltage & Current Query		15ms
		Setting & Query		32ms
State Storage Memory			Five user-configurable(voltage,current)stored states	
Operation Temperature Range			0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling			Isolation AC & DC FAN	
Output Terminal Isolated (maximum, from chassis ground)			±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard	단상 220V ± 10% 50~60Hz		
		3상 380V ± 10% 50~60Hz		
	Option	단상 100V ± 10% 50~60Hz		
		단상 230V ± 10% 50~60Hz		
Calibration Interval	Recommended		1 year	
Dimensions (19-inch compatible)			600mm(W) * 800mm(H) * 750mm(D)	
Maximum Input Power(full load)			12872.1W	
Weight	Net weight		170kg	
	Gross weight		180kg	

※ 주문자 사양 모델은 spec변경이 이루어질 수 있습니다.