

SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-18300S



ODA

TECHNOLOGIES
www.odacore.com

Parameter		Specifications		
Output rating(@0°C ~ 40°C)		0 to 18V / 0 to 300A		
Output WATT		5.4 KW		
Programming Accuracy (@25°C ±5°C)±(%of output + offset)	Voltage	0.2% + 200mV		
	Current	0.2% + 1.5A		
Readback Accuracy (@25°C ±5°C)±(%of output + offset)	Voltage	0.2% + 200mV		
	Current	0.2% + 1.5A		
Ripple and Noise(20Hz to 20MHz)	Voltage	≤ 10mVp-p		
	Current	≤ 10mArms		
Load Regulation (@25°C ±5°C)±(%of output + offset)	Voltage	0.01% + 30mV		
	Current	0.01% + 10mA		
Line Regulation (@25°C ±5°C)±(%of output + offset)	Voltage	0.01% + 30mV		
	Current	0.01% + 10mA		
Resolution	Programming/Readback	≤ 5mV / ≤ 80mA		
	Display Meter	100mV(3-DIGIT) / 1A(3-DIGIT)		
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage	0.02% + 10mV		
	Current	0.05% + 100mA		
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage	0.1% + 5mV		
	Current	0.2% + 10mA		
Transient Response Time		Less than 50μs for output to recover to within 50mV following a change in output current from full load to half load or vice versa		
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 120ms	
		Falling time	≤ 3.6s	
	Half load	Rising time	≤ 120ms	
		Falling time	≤ 15ms	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF	No overshoot, undershoot : ≤0V ~ ≥ -0.3V		
	Voltage Output Setting	No overshoot, No undershoot		
Remote Interface		RS232C Standard (RS485 Option)		
Programming Language		SCPI(Standard Commands for Programmable Instruments)		
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting	10ms	
		Voltage & Current Query	12ms	
		Measurement	Voltage & Current Query	
		The Other	Setting & Query	
State Storage Memory		Five user-configurable(voltage,current)stored states		
Operation Temperature Range		0°C ~ 40°C for full rated output. At higher temperatures the output current is derated linearly to 50% at 55°C maximum temperature		
Cooling		Isolation AC & DC FAN		
Output Terminal Isolated (maximum, from chassis ground)		±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals		
AC Input Ratings	Standard	단상 220V ± 10% 50~60Hz		
		3상 380V ± 10% 50~60Hz		
		단상 100V ± 10% 50~60Hz		
		단상 230V ± 10% 50~60Hz		
Calibration Interval	Recommended	1 year		
Dimensions (19-inch * 18U Standard Rack Case)		600mm(W) * 1000mm(H) * 750mm(D)		
Maximum Input Power(full load)		16208.4W		
Weight	Net weight	180kg		
	Gross weight	190kg		

* 주문자 사양 모델은 spec변경이 이루어질 수 있습니다.