

# SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-18200S



# ODA

TECHNOLOGIES  
www.odacore.com

Parameter		Specifications	
Output rating(@0℃ ~ 40℃)		0 to 18V / 0 to 200A	
Output WATT		3.6 KW	
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage	0.2% + 200mV	
	Current	0.2% + 1A	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage	0.2% + 200mV	
	Current	0.2% + 1A	
Ripple and Noise(20Hz to 20MHz)	Voltage	≤ 10mVp-p	
	Current	≤ 10mArms	
Load Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage	0.01% + 30mV	
	Current	0.01% + 10mA	
Line Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage	0.01% + 30mV	
	Current	0.01% + 10mA	
Resolution	Programming/Readback	≤ 5mV / ≤ 50mA	
	Display Meter	100mV(3-DIGIT) / 1A(3-DIGIT)	
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage	0.02% + 10mV	
	Current	0.05% + 100mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage	0.1% + 5mV	
	Current	0.2% + 10mA	
Transient Response Time		Less than 50μs for output to recover to within 50mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 120ms
		Falling time	≤ 3.6s
	Half load	Rising time	≤ 120ms
		Falling time	≤ 15ms
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF	No overshoot, undershoot : ≤ 0V ~ ≥ -0.3V	
	Voltage Output Setting	No overshoot, No undershoot	
Remote Interface		RS232C Standard (RS485 Option)	
Programming Language		SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting	10ms
		Voltage & Current Query	12ms
	Measurement	Voltage & Current Query	15ms
	The Other	Setting & Query	32ms
State Storage Memory		Five user-configurable(voltage,current)stored states	
Operation Temperature Range		0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling		Isolation AC & DC FAN	
Output Terminal Isolated (maximum, from chassis ground)		±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard	단상 220V ± 10% 50~60Hz	
		3상 380V ± 10% 50~60Hz	
	Option	단상 100V ± 10% 50~60Hz	
		단상 230V ± 10% 50~60Hz	
Calibration Interval	Recommended	1 year	
Dimensions (19-inch * 18U Standard Rack Case)		600mm(W) * 800mm(H) * 750mm(D)	
Maximum Input Power(full load)		9279.1W	
Weight	Net weight	120kg	
	Gross weight	135kg	