

# SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-8050S



# ODA

TECHNOLOGIES  
www.odacore.com

Parameter			Specifications	
Output rating(@0℃ ~ 40℃)			0 to 80V / 0 to 50A	
Output WATT			4.0 KW	
Programming Accuracy	Voltage		0.3% + 500mV	
(@25℃ ±5℃)±(%of output + offset)	Current		0.2% + 250mA	
Readback Accuracy	Voltage		0.3% + 500mV	
(@25℃ ±5℃)±(%of output + offset)	Current		0.2% + 250mA	
Ripple and Noise(20Hz to 20MHz)	Voltage		≤ 5mVp-p	
	Current		≤ 10mArms	
Load Regulation	Voltage		0.01% + 5mV	
	Current		0.01% + 5mA	
Line Regulation	Voltage		0.01% + 5mV	
	Current		0.01% + 5mA	
Resolution	Programming/Readback		≤ 22mV / ≤ 15mA	
	Display Meter		100mV / 100mA	
Temperature Coefficient ±(%of output + offset)	Voltage		0.02% + 5mV	
After a 30-minute warm-up	Current		0.05% + 10mA	
Stability ±(%of output + offset)	Voltage		0.1% + 8mV	
After a 1 hour warm-up	Current		0.2% + 10mA	
Transient Response Time			Less than 50μs for output to recover to within 50mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 120ms	
		Falling time	≤3.6s	
	Half load	Rising time	≤ 120ms	
		Falling time	≤ 15ms	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF	No overshoot, undershoot : ≤0V ~ ≥ -0.3V		
	Voltage Output Setting	No overshoot, No undershoot		
Remote Interface			RS232C Standard (RS485 Option)	
Programming Language			SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting	10ms	
		Voltage & Current Query	12ms	
	Measurement	Voltage & Current Query	15ms	
	The Other	Setting & Query	32ms	
State Storage Memory			Five user-configurable(voltage,current)stored states	
Operation Temperature Range			0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling			Isolation AC FAN	
Output Terminal Isolated (maximum, from chassis ground)			±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard	단상 220V ± 10% 50~60Hz		
		3상 380V ± 10% 50~60Hz		
	Option	단상 100V ± 10% 50~60Hz		
		단상 230V ± 10% 50~60Hz		
Calibration Interval	Recommended	1 year		
Dimensions (19-inch compatible)			426mm(W) * 265mm(H) * 650mm(D)	
Maximum Input Power(full load)			10305.6W	
Weight	Net weight	135kg		
	Gross weight	145kg		

※ 주문자 사양 모델은 spec변경이 이루어질 수 있습니다.