

SPECIFICATIONS

Programmable DC Power Supply

MODEL : ORS-303A



ODA

TECHNOLOGIES
www.odacore.com

Parameter		Specifications
Output rating(@0℃ ~ 40℃)	Voltage	0 to 30V
	Current	0 to 3A
Output Setting(@0℃ ~ 40℃) (by using variable volume knob)	Voltage	0 to ≤ 30V ~ ≤32V
	Current	≤ 20mA to ≤ 3A ~ ≤ 3.2A
Output WATT		90W
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage	0.4% + 2dgt
	Current	0.4% + 2dgt
Display Resolution (FND Display)		100mV / 10mA
Ripple and Noise(20Hz to 20MHz)	Voltage	≤ 0.5mVrms
	Current	≤ 2mArms
Load Regulation ±(%of output + offset)	Voltage	0.1% + 20mV
	Current	0.1% + 5mA
Line Regulation ±(%of output + offset)	Voltage	0.1% + 20mV
	Current	0.1% + 5mA
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage	0.2% + 3mV
	Current	0.5% + 3mA
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage	0.2% + 2mV
	Current	0.5% + 5mA
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF	No overshoot, No undershoot
	Voltage Output Setting	No overshoot, No undershoot
Operation Temperature		0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature
Cooling		Nature air cooling
AC Input Ratings(Include select switch)		115V ± 10% 50~60Hz
		230V ± 10% 50~60Hz
Calibration interval (Recommended)		1 year
Dimensions		130mm(W) * 165mm(H) * 310mm(D)
Maximum Input Power(full load)		271W
Weight	Net weight	4kg
	Gross weight	5.5kg